

1Exx - Carbon/Epoxy Laminat

Material number 001Exx

Page: 1 of 7

1. Product and company identification**Product identifier**

Trade name: 1Exx - Carbon/Epoxy Laminat

Relevant identified uses of the substance or mixture and uses advised against

General use: Article for orthopedic procedures

Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care

Street/POB-No.: 3820 W. Great Lakes Drive

Postal Code, city: Salt Lake City, UT 84120
USA

WWW: www.ottobockus.com

Telephone: +1 (801) 956-2400

Telefax: +1 (801) 956-2401

Dept. responsible for information:

Quality Department,

Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),

Email: USRegulatory@ottobock.com

Additional information: This safety data sheet pertains to the following products:

1E42, 1E43 - LuXon Max DP

1E50, 1E51 - Advantage DP2

1E61, 1E62, 1E63, 1E64, 1E65, - Springlite II

1E66 - Springlite II Pediatric Foot

1E80, 1E81, 1E82 - Chopart

1E90 - Sprinter Foot

Corporate headquarters:

Ottobock SE & Co. KGaA

Max-Näder-Straße 15

Duderstadt

Germany

Emergency phone number**CHEMTREC, Telephone: +1 (800) 424-9300****2. Hazards identification****Emergency overview**Appearance: Form: solid
Color: black

Odor: odorless

Classification: This substance is classified as not hazardous.

Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

1Exx - Carbon/Epoxy Laminat

Material number 001Exx

Page: 2 of 7

Hazards not otherwise classified

Processing, e.g. by cutting, sawing or grinding, can produce particles and dust. For risks which have to be observed thereby, see section 7: Handling, section 8: Exposure controls / personal protection and section 11: Toxicology.
see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: Article: mixture with Carbon fibers, Epoxy resin - Laminate, Polyurethane (cured)

4. First aid measures

In case of inhalation: In case of troubles after inhalation of dust: Provide fresh air. Seek medical treatment in case of troubles.

Following skin contact: In case of dust: Remove residues with soap and water. In case of skin irritation, consult a physician.

After eye contact: In case of dust: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing: Swallowing is not regarded as a possible way of exposition.
In case of dust: Rinse mouth with water. Seek medical treatment in case of troubles.

Most important symptoms/effects, acute and delayed

In case of inhalation:
For mechanical processing: dust formation. Can irritate the mucous membrane.
In case of ingestion: In case of dust: Can damage your health.

After eye contact:
In case of dust: Upon direct contact with eyes may cause burning, tearing, redness.

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:

No data available

Auto-ignition temperature: No data available

Suitable extinguishing media:

Water spray jet, foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet.

Specific hazards arising from the chemical

In case of fire may be liberated: nitrogen oxides (NOx), carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

1Exx - Carbon/Epoxy Laminat

Material number 001Exx

Additional information: Cool endangered containers with water spray and, if possible, remove from danger zone. Use a water fog to control vapors. Do not breathe fumes. Do not allow fire water to penetrate into surface or ground water. For that reason, provide adequate installations to retain fire water. Disposal of contaminated water and earth must take place according to local regulations.

6. Accidental release measures

Personal precautions: Avoid generation of dust.
 In case of dust: Do not breathe dust. Wear appropriate protective equipment.

Environmental precautions: Discharge into the environment must be avoided.

Methods for clean-up: Dust: Take up mechanically, placing in appropriate containers for disposal. Dispose of waste according to applicable legislation.

7. Handling and storage

Handling

Advices on safe handling: For mechanical processing:
 Provide adequate ventilation. Avoid generation of dust.
 Wear appropriate protective equipment. The use of local exhaust ventilation is recommended. When using do not eat, drink or smoke.

Precautions against fire and explosion:
 Carbon Fiber is electrically conductive. It can cause short circuits within electrical equipment, if material dusts penetrate into the ambient air.
 Take standard precautions to prevent fire.

Storage

Requirements for storerooms and containers:
 Store at room temperature. Keep away from heat.

Hints on joint storage: Keep away from food, drink and animal feedingstuffs.

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

Type	Limit value
USA: ACGIH: TWA	10 mg/m ³
USA: ACGIH: TWA	3 mg/m ³
USA: OSHA: TWA	15 mg/m ³
USA: OSHA: TWA	5 mg/m ³

Engineering controls

For mechanical processing:
 Provide adequate ventilation. The use of local exhaust ventilation is recommended.
 See also information in chapter 7, section storage.

1Exx - Carbon/Epoxy Laminat

Material number 001Exx

Personal protection equipment (PPE)

- Eye/face protection For mechanical processing:
Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010
- Skin protection For mechanical processing: Wear suitable protective clothing.
For mechanical processing:
Protective gloves according to OSHA Standard - 29 CFR: 1910.138
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Respiratory protection: For mechanical processing:
Dust mask.
Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded.
OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2
- General hygiene considerations:
Avoid generation of dust.
Wash hands before breaks and after work.

9. Physical and chemical properties

Information on basic physical and chemical properties

- Appearance: Form: solid
Color: black
- Odor: odorless
- Odor threshold: No data available
- pH value: No data available
- Melting point/freezing point: No data available
- Initial boiling point and boiling range: No data available
- Flash point/flash point range: No data available
- Evaporation rate: No data available
- Flammability: No data available
- Explosion limits: No data available
- Vapor pressure: No data available
- Vapor density: No data available
- Density: No data available
- Water solubility: insoluble
- Partition coefficient: n-octanol/water: No data available
- Auto-ignition temperature: No data available
- Thermal decomposition: No data available
- Additional information: No data available

10. Stability and reactivity

- Reactivity: No data available.
- Chemical stability: Stable under recommended storage conditions.
- Possibility of hazardous reactions
No hazardous reaction when handled and stored according to provisions.

1Exx - Carbon/Epoxy Laminat

Material number 001Exx

Page: 5 of 7

Conditions to avoid: Carbon Fiber is electrically conductive. It can cause short circuits within electrical equipment, if material dusts penetrate into the ambient air.
Keep away from heat. Avoid generation of dust.

Incompatible materials: No data available

Hazardous decomposition products:
In case of fire may be liberated: nitrogen oxides (NOx), carbon monoxide and carbon dioxide.

Thermal decomposition: No data available

11. Toxicological information

Toxicological tests

Toxicological effects: Acute toxicity (oral): Lack of data.
Acute toxicity (dermal): Lack of data.
Acute toxicity (inhalative): Lack of data.
Skin corrosion/irritation: Lack of data.
Serious eye damage/irritation: Lack of data.
Sensitisation to the respiratory tract: Lack of data.
Skin sensitisation: Lack of data.
Germ cell mutagenicity/Genotoxicity: Lack of data.
Carcinogenicity: Lack of data.
Reproductive toxicity: Lack of data.
Effects on or via lactation: Lack of data.
Specific target organ toxicity (single exposure): Lack of data.
Specific target organ toxicity (repeated exposure): Lack of data.
Aspiration hazard: Lack of data.

Other information: For mechanical processing:
Dust: mild irritant.
Possible in traces: Formation of WHO-fibers. classification WHO-fibers: Causes concern for man owing to possible carcinogenic effects.

Symptoms

In case of inhalation:
For mechanical processing: dust formation. Can irritate the mucous membrane.
In case of ingestion: In case of dust: Can damage your health.
After eye contact:
In case of dust: Upon direct contact with eyes may cause burning, tearing, redness.

12. Ecological information

Ecotoxicity

Further details: No data available

Mobility in soil

No data available

1Exx - Carbon/Epoxy Laminat

Material number 001Exx

Page: 6 of 7

Persistence and degradability

Further details: No data available

Additional ecological information

Volatile organic compounds (VOC):

0 % by weight

General information: Discharge into the environment must be avoided.

13. Disposal considerations**Product**

Recommendation: Incinerate according to applicable local, state and federal regulations.

Contaminated packagingRecommendation: Dispose of waste according to applicable legislation.
Non-contaminated packages may be recycled.**14. Transport information****USA: Department of Transportation (DOT)**

Proper shipping name: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information**National regulations - U.S. Federal Regulations**

Refer to 29 CFR Part 1910 subpart q - Welding, Cutting, Brazing 1910.252.

National regulations - Great Britain

Hazchem-Code: -

1Exx - Carbon/Epoxy Laminat

Material number 001Exx

Page: 7 of 7

16. Other information

Hazard rating systems:



NFPA Hazard Rating:

Health: 0 (Minimal)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 0 (Minimal)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Reason of change: Changes in section 1.3: Corporate headquarters

Date of first version: 11/12/2008

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.