

1C70 *Evanto*. Feel the flow.

Evanto was designed for active individuals who navigate varied indoor and outdoor environments and place a high value on a natural walking feeling, increased endurance and a high degree of comfort on uneven terrain.

Designed for optimal outcomes

- **Evanto's** innovative design stores the highest amount of energy at heel strike and returns it at toe off for enhanced forward propulsion.*
- High-performance wedges allow for up to 24 mm of shock absorption at heel strike.*
- When going down stairs or stepping off curbs, **Evanto** provides up to 9 mm of vertical shock absorption.*
- Excellent multi-axial compliance provides stability and a high degree of comfort with up to 20° of sagittal plane motion, +/- 10° of m-l flexibility, and +/- 4° of torsional motion.*
- Customizable forefoot and heel behavior to meet individual user needs.
- Waterproof, protected against fresh, salt and chlorinated water.

*Comparison to state-of-the-art energy storing and return prosthetic feet like Taleo

More than a foot. A foundation.



waterproof

Technical data

Mobility grade	3
Max. body weight	275 lbs (125 kg)
Sizes	22 – 30 cm
Weight without footshell*	16 oz (450 g)
Footshell shape	Slim shape (S): sizes 22-27 cm Normal shape: sizes 22-30 cm
Footshell color	beige (4), light brown (15), midnight black (7, Slim only)
Weight with footshell*	25.5 oz (725 g)
Build height*	3 1/4" (82 mm)

* Reference size is 26 cm.

ottobock.



Shock absorption
for user comfort

Multi-axial flexibility
for adaptation to
uneven terrain

Innovative energy
management
for improved
endurance

1C70

Order form.

ottobock.

Customer

Customer no.

Company

Street

Zip/Postal code City

State/Province

O&P professional

Shipping address (if different from customer address)

Customer no.

Company

Street

Zip/Postal code City

State/Province

Customer ref.

Selection of the spring stiffness relative to body weight and foot size

Slim and normal footshell available
 Normal footshell available

Body weight \ Foot size (cm)	22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm
up to 128 lbs (58 kg)	1	1	1	1	-	-	-	-	-
129-159 lbs (59-72 kg)	2	2	2	2	2	2	2	2	2
160-190 lbs (73-86 kg)	3	3	3	3	3	3	3	3	3
191-220 lbs (87-100 kg)	4	4	4	4	4	4	4	4	4
221-275 lbs (101-125 kg)	-	-	-	-	5	5	5*	5*	5*

* Do not combine this configuration with a 3C88-3 C-Leg or a 3C98-3 C-Leg.

Bale width of the footshells (+/- 2 mm)

Size	Slim Shape	Normal Shape
22 cm	75 mm	80 mm
23 cm	77 mm	85 mm
24 cm	80 mm	90 mm
25 cm	83 mm	90 mm
26 cm	85 mm	95 mm
27 cm	88 mm	95 mm
28 cm	-	98 mm
29 cm	-	100 mm
30 cm	-	100 mm

Example for ordering with the 2C70=* footshell (normal shape)

1C70=R26-4-P/4

Article no.	Side	Size	Stiffness	Color
1C70	=		-	P /
	Side	Size (cm)	Stiffness	Color
	R Right	22, 23, ..., 30	1, 2, ..., 5	4 Beige
	L Left			15 Light brown

Example for ordering with the 2C70=*S footshell (slim shape)

1C70=R26-4-P/4S







Article no.	Side	Size	Stiffness	Color	Shape
1C70	=		-	P /	S
	Side	Size (cm)	Stiffness	Color	
	R Right	22, 23, ..., 27	1, 2, ..., 5	4 Beige	
	L Left			7 Midnight black	
				15 Light brown	

To order the foot module and footshell separately, please refer to our online shop and catalog.



The scope of delivery includes the 1C70 foot module, the 2C70 footshell including connection cover, the upper wedge set (comprising two wedges with different degrees of hardness), the lower wedge set (comprising two wedges with different degrees of hardness) and a black Spectra sock.

Recommended combinations**

TT	TF
 4R136=EL One-way valve + 453A30/40 ProFlex Plus sleeve + 6Y95 Caleo 3D Liner or 4R180 Harmony P4 + 453A30/40 ProFlex Plus sleeve + 6Y512=*-P Uneo Fresh Liner	 5A60 Varos Socket and 6Y200 Varos Liner or Laminated socket + 6Y110 Skeo Sealing + 21Y21 ClickValve
 4R11=* Quickchange	 3C60* Kenevo, 3R85* Dynion, 3C98* C-Leg, 3B1* Genium or 3B5* Genium X3  4R57=WR Waterproof Rotation Adapter 4R11=* Quickchange
	 3F1=* + 99B120=* Functional cosmesis

** All components are sold separately and are available Ottobock products that are compatible with the 1C70 *Evanto* foot, which helps ensure optimal performance. Practitioners need to select components based upon individual patient criteria.