ottobock.

Genium X4 – Prosthetic knee joint. Order form.

Contact person	Customer no.	Date
Customer	Shipping addre	SS (if different from customer address)
Company	Company	
Address	Address	
City/State	City/State	
Zip/Postal code	Zip/Postal code	
Email	Email	

Gender	Female	Male	Mobility Grade Mobility Grade 2
Weight	lbs		Mobility Grade 3
Foot size	cm		Mobility Grade 4
Side of amputation	left right	bilateral	Amputation Level
Prosthetic attachment to residual limb	Conventional s		Knee Disarticulation Transfemoral Hip Disarticulation / Hemipelvectomy

Fitting

Initial fitting (of microprocessor controlled knee joint made by Ottobock previous prosthetic knee joint is known:

Osseous anchored implant

Manufacturer Model previous prosthetic knee joint is unknown no previous prosthetic knee joint

Follow-up fitting (of microprocessor controlled knee joint made by Ottobock) → previous microprocessor controlled knee joint

Model

Serial number

ottobock.

Quickchange connecting element

with thread

Genium X4 – Prosthetic knee joint. Order form.

Knee joint

	3B5-4=P	Genium X4		3B5-4=ST	Genium X4 – for long residual limb
Includes the fo	llowing additional	components: 757L48=1 AC Adapter (EU and U	S compatible), 7	57L47=1 USB Adap	ter for charging, 4H110=7.5 Flexion Stop 7.5°.

Includes the following additional components: 757L48=1 AC Adapter (EU and US compatible), 757L47=1 USB Adapter for charging, 4H110=7.5 Flexion Stop 7.5°, 4H110=15 Flexion Stop 15° (pre-assembled), 4H110=22.5 Flexion Stop 22.5°.

Warranty (please choose one)

	SP-3B5-4=3	3-year warranty package		SP-3B5-4=6	6-year warranty package
r standar	d warranty packag	e included at the time of product purchase. 6-	-year extended v	varranty can be p	urchased at the time of product purchase.

3-year standard warranty package included at the time of product purchase. 6-year extended warranty can be purchased a A 3 to 6 year warranty extension can be purchased within 36 months of initial purchase.

Electronic Tube Adapter

2R68=280	AXON Tube adapter (waterproof and corrosion resistant)		2R69=280	AXON Tube adapter (torsion unit= weatherproof, not corrosion resistant)
----------	---	--	----------	--

Connection components

4047-5.0	Defit edentes for landation and an	4044-0 4 2	
4R47=5.0	Refit adapter for lamination anchor	4R11=P-1-3	Quickchange set with pyramid
4R48=5.0	Refit socket adapter	4R11=R-1-3	Quickchange set with pyramid receiver
4R57=WR	Rotation adapter (waterproof and corrosion resistant)	4R11=ST-1-3	Quickchange set with thread
4R57=WR-ST	Rotation adapter screw top (waterproof and corrosion resistant)	4R11=R-3-2	Quickchange base element with pyramid receiver
		4R11=P-1-1	Quickchange connecting element with pyramid
		4R11=R-1-1	Quickchange connecting element with pyramid receiver

4R11=ST-1-1

Foot components

	1A1-2	Empower		1C63	Triton Low Profile ²
	1B1-2	Meridium		1C64	Triton Heavy Duty ²
	1C30-1	Trias		1C68	Triton side flex ²
	1C40	C-Walk		1C70	Evanto
	1C60	Triton		1D35	Dynamic Motion
	1C61	Triton Vertical Shock		1E56	Axtion
	1000	Tuite a lla marcana		1E95	Challenger
	1C62	Triton Harmony		IE35	Chattenger
	shell beige	3		1235	Chattenger
	shell beige	light brown ¹		F21	Maverick Xtreme AT ²
Color of foot Shape of foo	t shell beige b tshell slim ¹	light brown¹ normal			
	shell beige otshell slim ¹ 1C50	light brown ¹ normal Taleo ²		F21	Maverick Xtreme AT ²
	shell beige btshell slim ¹ 1C50 1C51	light brown ¹ normal Taleo ² Taleo Vertical Shock	Activity level	F21 F22 F23	Maverick Xtreme AT ² Maverick Comfort AT ²
	shell beige stshell slim ¹ 1C50 1C51 1C52	light brown ¹ normal Taleo ² Taleo Vertical Shock Taleo Harmony	Activity level Color of foots	F21 F22 F23 low	Maverick Xtreme AT ² Maverick Comfort AT ² Maverick Vertical Shock

Color of footshellbeigelight brown1Shape of footshellslim1normal

In combination with a prosthetic knee joint, some foot sizes and stiffnesses may be excluded. Please follow the information in the foot order sheet and the instructions for use. In case of any questions, please contact Ottobock customer service.

¹Not available for all feet and/or sizes. Please visit our homepage for more information.

 $^{\rm 2}\,{\rm Recommended}$ combination, because of water & corrosion resistant components.

ottobock.

Genium X4 – Prosthetic knee joint. Order form.

Cover Solutions

4P100=7	Genium X4 Protective cover, short	3D13=1	Thigh kit/	Magnetic clo	sure
4P110=7	Genium X4 Protective cover, long	3F2=0	Functiona	l cosmesis G	ienium X4
4P112=1	Functional knee part	99B122	Functiona	l stocking	
			Size Color	S beige-4	L light brown-15

Accessories Included in scope of delivery.

-	757L48=1	AC Adapter	4H110=7.5	Flexion Stop 7.5°
-	757L47=1	USB Adapter for charging	4H110=15	Flexion Stop 15°
			4H110=22.5	Flexion Stop 22.5°

The General Terms and Conditions of Ottobock SE & Co. KGaA apply. The expected lifetime given compliance with the prescribed maintenance intervals is 6 years. For additional information please contact / visit:

Date

Place

Signature